


5 pin

D43 ↓24.6% ↑75.4% Φ: 6900 lm



Connected load

Work equipment

Power consumption

Luminous flux

Luminous efficiency¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Glare control

Life expectancy LED

Chromaticity tolerance LED

At-risk group

System of protection/Class

Technology

Operation

Housing

Light source cover

Mains lead

Design

Fastening

Maximum ambient temperature

Weight without/incl. packaging

Packaging dimensions

EAN

Special features

220 - 240 V; AC; 50 Hz; 60 Hz

Power supply unit

approx. 61 W

approx. 6.900 lm

approx. 113 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct/indirect

Diffusor

L80B50 50.000h

< 3 SDCM

RG0/1

IP 20; I

Switchable

Switch

Sectional aluminium; Anodised; Aluminium
coloured anodised

Acrylic (PMMA); White opal

Connector; 5 pin

mounted version

Wall bracket

25 °C

6,9; approx. 8,9 kg

133 mm; approx. 400 mm; 1.185 mm

4013330146337

General light, indirect, 3000K, Ra≥80; Reading light,
direct, 3,00K, Ra≥80; DIN EN 60598-2-25

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear